

## REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1-14 in the underlying PCT Application No. PCT/DE99/03219, and adds new claims 15-28. The new claims conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

The amendments to the specification and abstract reflected in the substitute specification are to conform the specification and abstract to U.S. Patent and Trademark Office rules, and do not introduce new matter into the application.

The underlying PCT Application No. PCT/DE99/03219 includes an International Search Report and a revised International Search Report, copies of which is included. The Search Reports includes a list of documents that were considered by the Examiner in the underlying PCT application.


The underlying PCT Application No. PCT/DE99/03219 also includes an International Preliminary Examination Report, issued September 1, 2000. A translation of the International Preliminary Examination Report is included herewith.

It is respectfully submitted that the present invention is new, non-obvious, and useful. Prompt consideration and allowance of the claims are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

Dated: 5/31/01

By:   
Richard L. Mayer  
Reg. No. 22,490

One Broadway  
New York, NY 10004  
(Tel) (212) 425-7200  
(Fax) (212) 425-5288  
CUSTOMER NO. 26646

DRS

A1

~~METHOD AND DEVICE FOR DETERMINING A FUTURE TRAVEL-PATH  
AREA OF A VEHICLE~~Field of the Invention

The present invention relates to a method [as well as]  
and a device for determining a future travel-path area of  
5 a motor vehicle. It can be applied, for example, in [the]  
an adaptive speed or distance control of a vehicle, in an  
adaptive headlight leveling adjustment, or simply in  
detecting critical situations. The [presupposition is  
that the] vehicle is furnished with at least one sensor,  
10 which can detect, [and] or at least determine the  
position of, vehicles traveling ahead and stationary  
objects in the forward field of the vehicle. Sensors of  
this type can be configured, for example, as radar,  
laser, or video sensors. The present invention [is] can  
15 be used [advantageously] in connection with an adaptive  
speed or distance control system of a vehicle[, because a  
sensor of this type is already present in this  
application].

Background Information

In past years, numerous publications have appeared, which  
deal with an automatic control system for the speed of a  
motor vehicle while taking into consideration the  
25 distance with respect to vehicles traveling ahead.  
Systems of this type are frequently termed Adaptive  
Cruise Control (ACC) or, [in German,] adaptive or dynamic  
speed regulators. One fundamental problem in systems of  
this type, in view of contemporary traffic patterns, is  
30 an automatic decision as to which vehicle of a plurality  
of vehicles traveling ahead is relevant, or most

relevant, for the speed or distance control system. This decision is particularly [difficult in the event that] challenging when the road on which the controlled vehicle is moving is multi-lane and curvy. In this case, a distance sensor, which is used, inter alia, for detecting vehicles traveling ahead, usually also detects vehicles that are located on neighboring lanes and that therefore have only minor relevance for a distance control system.

Therefore, in an ACC system, there exists a need to determine a future course path, or a future travel-path area, of the controlled vehicle, in order, once this area is known, to determine the [specifically] most relevant vehicles traveling ahead or, conversely, to determine the obstacle that at an instantaneous time point is the most dangerous. Both variables, as well as the course path and the travel-path area, are fundamentally oriented on the direction of the road, but in the optimal case they also take into account, if appropriate, any lane changing or turning behavior carried out by the controlled vehicle. In this context, the concept "future travel-path area" is distinguished in what follows from the concept "future travel-path" in that the former contains the entire spatial area in which the controlled vehicle will probably move. This means that it also takes into account in each case the width required by the motor vehicle.

[Currently known] Conventional solutions to the aforementioned [formulation of the] problem are described, for example, in the publication "Adaptive Cruise Control -- System Aspects and Development Trends" by Winner, Witte, et al., published as SAE Technical Papers Series No. 961010 at the SAE of February 26-29, 1996. In that publication, the simplest way to predict a future course of a controlled vehicle is to assume movement in a straight line. However, [it is obvious

that] this type of prediction does not function in the case of curves or lane changes. A more complex case, which nevertheless delivers sufficient results for wide areas, is to assume a course having a constant curvature.

5 The latter is determined, for example, on the basis of a difference of wheel speeds, a steering or steering wheel angle, transverse accelerations, and/or yaw rates.

Corresponding methods [are known from] can be found in the field of driving dynamic control systems. [One

10 disadvantage in] In this method [is that], the future course path or travel-path area is only estimated[,] in each case on the basis of the present course. Therefore, here too, errors arise in response to every change of

15 course, for example, in driving into or out of curves. A further possibility for predicting a course path, which is also mentioned in the cited publications, is the application of navigation systems. However, the limits of this method depend on how up-to-date and precise the

20 available maps are and on the capacity of the system to determine[,] in each case[,] the current position of the vehicle. The prediction [is particularly] may be

unreliable in construction zones or on new roads. As a further possibility, [mention is made] in the above-cited publication [of], a prediction of the road course or the

25 lane based on radar data is mentioned. Stationary objects are used such as reflectors or crash barriers, which are detected by a signal processor, in order to reconstruct the road borders. However, according to the publication, little is known regarding the quality and reliability of

30 this method.

In U.S. Patent No. 4,786,164, a system and a method are described for detecting the distance between two vehicles which are moving in the same traffic lane. In this

35 context, the lane in which each of the two vehicles is moving is determined on the basis of a comparison of

angles at which reflectors that are placed on both sides of the road are detected. However, the method described here can only be used if suitable reflectors are actually present on both sides of the road, and is therefore dependent on infrastructure conditions.

In German Patent Application No. 196 14 061 A1, a system is described for controlling the distance to a vehicle traveling ahead on the basis of an adjustable probability distribution. This [described] system has a curvature determination device, in which the curvature of a road is determined on the basis of a steering angle and a vehicle speed. To improve the reliability, according to a first modification, the steering angle is determined on the basis of the motion of a specified stationary object. For this purpose, the locations of a stationary object relative to a system vehicle in motion are monitored at uniform time intervals. The locations are then defined as a circular arc to calculate the curvature of the road on which the system vehicle is traveling. According to a second modification, a sharp curve of the road can also be detected on the basis of a stationary object. According to a fourth modification, the calculated curvature can be increased or reduced if a turning signal indicates the right or left direction. According to a tenth modification, it is possible, on the basis of a navigation system, for example, a GPS system, to determine whether a curve is present in a forward direction of the system vehicle.

[However, not one of the methods presented in this document removes the disadvantages already cited in detail.

From German Patent 41 33 882 A1, a method is known] German Patent No. 41 33 882 describes a method for

independently following a vehicle in the lane of a  
[quite] specific vehicle traveling ahead. For this  
purpose, using an electronic camera, the significant rear  
area of a leading vehicle is monitored and the sideways  
misalignment with respect to it is approximately  
determined. The goal [is] appears to be to obtain control  
signals for steering the vehicle carrying the camera.

[From] German Patent No. 43 41 689 [A1,] describes a  
system [is known] for detecting a vehicle traveling  
ahead. The point of departure is a center line, which  
represents the extension of the vehicle axis. Around this  
line, areas of varying probabilities are defined, which  
are used to recognize a detected target as being located  
in the lane or as being irrelevant. The curvature of the  
road ahead is calculated on the basis of the current  
steering angle and of the current speed. A displacement  
is determined as a function of this predicted curvature,  
at the distance at which another vehicle has been  
detected, and the previously determined probability  
distribution is shifted by this value.

[From the as yet not pre-published German patent  
application 197 22 947.6-32,] German Patent Application  
No. 197 22 947 describes a method and a device [are  
known] for determining a future travel-path area of a  
vehicle. There, on the basis of the detected positions of  
the vehicles traveling ahead, the course paths of the  
latter are observed and in each case the transverse  
offset is determined with respect to the first vehicle's  
own position. This occurs in each case at the [time]  
point in time at which the first vehicle has passed the  
point at which a first position of the corresponding  
vehicle traveling ahead had been stored in memory. Based  
on the knowledge of this transverse offset and of the  
stored course paths of the vehicles traveling ahead, a

future travel-path area of the first vehicle can be determined.

[The disadvantage of the previous] These methods and devices appear to describe approaches to determining the future travel-path area of a first vehicle [can be seen in the fact that] using the earliest possible time point for determining a travel-path area [is] as the time point at which a point is passed at which a position of a vehicle traveling ahead has been detected.

[Objective, Solution, and Advantages] Summary of the Invention

The [objective of the] present invention[, accordingly, is to indicate] provides a method and a device[, based thereon, using which] for reliably determining a future travel-path area of a first vehicle [can be reliably determined. This]. According to the present invention, this travel-path area [should be] is able to be determined reliably and in a timely fashion, especially when vehicles traveling ahead have been detected for the first time.

According to the present invention, [this objective is achieved as a result of the fact that] the future travel-path area of the first vehicle is determined at least on the basis of a course path of a vehicle traveling ahead that is projected onto the position of the first vehicle. This means that the detected course path of the vehicle traveling ahead is projected into an area in front of the first vehicle, in which no measured positions of the vehicle traveling ahead are present.

[The advantage of the method according] According to the present invention [and of the device according to the

present invention can be seen in the fact that it is already possible to determine] the future travel-path area of the first vehicle before a position is reached at which a vehicle traveling ahead has been detected[. As a result of this invention, it is possible,] can be determined.

According to an embodiment of the present invention, in accordance with the speed of the first vehicle and the range of the distance sensor, it is possible to gain up to two seconds in comparison with previous methods and devices, in which it is already possible to determine the future travel-path area of the first vehicle. This can contribute to reducing the pressure on the driver of the first vehicle and to increasing general driving safety.

The course path of the vehicle traveling ahead can [advantageously] be projected up until the position at which the first vehicle is located. This allows the system the maximum exploitation of the stored data for determining the future travel-path area of the first vehicle.

According to [one preferred] an embodiment of the present invention, [for this purpose,] a transverse offset and/or a curvature is determined between the projected course path of the vehicle traveling ahead and the current course path of the first vehicle. Using the transverse offset and/or the curvature of the course path of the first vehicle with respect to the projected course path of the vehicle traveling ahead, a future travel-path area of the first vehicle is determined. This embodiment offers the advantage that, for determining the future travel-path area of the first vehicle, it is also possible to use a projected course path of a vehicle traveling ahead which is not moving in the same traffic



lane as the first vehicle.

[According to one advantageous refinement] In a further embodiment of the present invention, the future

5 travel-path area is determined on the basis of the projected course paths of a plurality of vehicles traveling ahead. In this context, a lane change of a single vehicle traveling ahead is filtered out using comparison, correlation, or an average of the projected  
10 course paths of all vehicles traveling ahead. This refinement, especially given the presence of many other traffic participants, leads to improved reliability of the method [according to the present invention and of the] and device according to the present invention.

15 Therefore, all projected course paths of vehicles traveling ahead can be used for determining the travel-path area of the first vehicle, which results in improving the reliability of the determined travel-path area.

20 [Furthermore, it is advantageous,] Further embodiments of the present invention provide at selected and/or freely selectable time points[, to compare] a comparison of the stored course paths of the vehicles traveling ahead with  
25 the current coordinate system of the first vehicle. [This has the advantage that the] The storage device can be exploited [very well] for recording the projected course paths of vehicles traveling ahead[, because a detected position of a vehicle traveling ahead, calculated with  
30 respect to the current coordinate system of the first vehicle, therefore represents a position relative to the first vehicle[, and the]. The data to be stored can be composed of, for example, only one distance and angle specification.

35 The course path of the vehicle traveling ahead [is

advantageously] can be projected using statistical analyses and/or mathematical interpolation methods on the stored relative positional data. This analytic approach, and this interpolation method, make possible a very precise determination of the course path to be projected.

[It is particularly advantageous to] Further embodiments of the present invention evaluate the projected course paths of the vehicles traveling ahead using at least one performance index[, ] which contains both statistical as well as non-predictable and predictable components. Therefore, it is [advantageously] possible to delete from the storage device a projected course path of a vehicle traveling ahead having a performance index that lies beneath a predetermined threshold value, and/or not to consider it for determining the future travel-path area of the first vehicle. In this manner, [on the one hand,] exploitation of the storage device is improved because data which are less well-suited for determining the future travel-path area of the first vehicle are deleted from the storage device. [On the other hand, it is therefore] It is possible not to use less suitable data in determining the travel-path area, which leads to a more precise determination.

According to [one refinement] a further embodiment of the present invention, the storage device is organized as a ring storage device. [This refinement has the advantage that] The memory management is simplified, and [therefore] determining the future course path of the first vehicle is accelerated. Especially in this type of storage organization, no shifting of data within the storage device is necessary. [In plain language] That is, the oldest stored data value for a course path of a vehicle traveling ahead is replaced by the currently detected value, and only a corresponding reference to the

storage location is changed.

[It is furthermore advantageous that] According to a further embodiment of the present invention, when the storage device is full, for storing at least one new course path of a further vehicle traveling ahead, in accordance with a further performance index which rests only on predictable components, the decision is made as to whether at least one of the previously stored course paths and/or the at least one new course path should be deleted. [This means that] That is, when the storage device is full, it is determined[,] using a performance index[,] whether a previously stored course path should be deleted[,] or whether the newly detected data have a worse index than all of the course paths stored in the storage device[,] and that therefore the newly stored data should be discarded.

According to [one advantageous refinement] a further embodiment of the present invention, the future travel-path area is limited on the basis of the positions of detected, stationary objects or on the basis of positions of detected, oncoming vehicles. This [refinement has the advantage that it is possible to sensibly limit] allows for sensibly limiting the determination of the future travel-path area of the first vehicle[,] which significantly increases the precision of the determined travel-path area. Furthermore, in this manner, further independent data can contribute to determining the future travel-path area.

According to [one particularly preferred] a further embodiment of the present invention, in addition to the first future travel-path area, determined in accordance with present invention, at least one further future travel-path area is determined on the basis of a steering

angle, a steering wheel angle, a yaw rate, a difference of wheel speeds, or a transverse acceleration of the controlled vehicle, or on the basis of stationary objects or of oncoming vehicles which are detected by the distance sensor of the first vehicle. On the basis of the first and the at least one further determined future travel-path area, a verified future travel-path area [is] can then be determined. [In plain language, this means that a] A future travel-path area of the controlled vehicle [is] can be determined on the basis of different methods that are independent of each other. By combining these individually determined future travel-path areas, errors individually arising in the [methods] methods/devices can be corrected, so that the verified future travel-path area contains an optimal prediction of the actual travel-path area.

[One particular advantage of the method according to] Certain embodiments of the present invention [and of the device according to the present invention is] provide that the future travel-path area is determined on the basis of measuring data which actually lie in the forward field of the controlled vehicle, and that these data are projected in the direction of the first vehicle's own position. In place of an estimation based on extrapolating an instantaneous situation, the situation actually existing in the forward field of the vehicle is evaluated. In this manner, it is especially possible to detect in a timely fashion the beginning or end of a curve. As a result, the error rate is significantly reduced compared with previously known methods. [A further advantage is that the method] Further, the present invention is independent of particular infrastructure conditions, such as specially provided reflectors on the road edge. However, if appropriate reflectors are present, they can be taken into account

accordingly. Furthermore, the [method] present invention  
can be realized without special expense in a vehicle  
which is equipped with an adaptive speed regulating  
system, in particular without requiring an additional  
5 image pick-up and image valuation unit.

[In plain language, the] The movement of one or a  
plurality of vehicles traveling ahead is observed for  
determining the future course path or travel-path area of  
10 the first vehicle. In this context, as long as a detected  
position of a vehicle traveling ahead is not reached by  
the first vehicle, the detected course path of the  
vehicle traveling ahead is projected in the direction of  
the first vehicle's own position. Therefore, determining  
15 the travel-path area for the first vehicle is possible  
even before a position has been reached at which a  
vehicle traveling ahead has been detected.

[Description of Exemplary Embodiments] Brief Description  
20 of the Drawings

[Below, exemplary embodiments of the present invention  
are discussed on the basis of a drawing. The following  
are the contents.

Figure 1 depicts a basic representation of a device]  
25 Figure 1 shows an embodiment according to the present  
invention[,];

[Figure 2 and Figure 3  
30 depict two block diagrams, as an explanation of the  
method] Figure 2 shows a block diagram of an  
embodiment according to the present  
invention[,];

[Figure 4 depicts] Figure 3 shows a block diagram of an  
35 embodiment according to the  
present invention;

Figure 4 shows a flowchart according to related art;

Figure 5 shows a flowchart according to the

[aforementioned] related art[,];

Figure [5 depicts a further] 6 shows a flowchart

according to the

[aforementioned

related art,] related

art; and

[Figure 6 depicts a further flowchart according to the

aforementioned related art, for a detailed explanation of  
the method, and

Figure 7 depicts a block diagram, as an explanation of

the method] Figure 7 shows a block diagram of an

embodiment according to the

present invention.

#### Detailed Description

Figure 1 [depicts] shows a device for carrying out the  
method according to the present invention. A distance  
sensor 10, for example, a radar or a laser sensor, is  
connected to an evaluation and control unit 11.

Evaluation and control unit 11 receives numerous further  
signals, of which, by way of example, an input 13 for the  
vehicle's own speed, an input 14 for a steering angle,  
and an input 15 for a yaw rate are depicted here.

Furthermore, evaluation and control unit 11 is connected  
to one or a plurality of actuators 12. The entire device

is installed in a first vehicle. Using distance sensor  
10, in accordance with [the known] conventional methods,  
vehicles traveling ahead, oncoming vehicles, as well as  
stationary objects on, and on both sides of, the roadway  
are detected. Corresponding measuring data are

pre-processed and are supplied to evaluation and control  
unit 11. The latter, in accordance with the method

described below, determines at least one future travel-path area of the first vehicle. In the context of an adaptive speed regulation, evaluation and control unit 11, via actuator or actuators 12, controls or regulates the speed of the vehicle. Alternatively, or as a supplement, the unit, via actuators 12, controls, for example, the headlight range or the light cone of the headlights of the vehicle, or it generates a warning signal for a critical situation.

Figure 2 [depicts] shows a two-lane road 20, on which two vehicles 21 and 22 are moving in the same direction. Reference numeral 21 designates the vehicle which has the device according to the present invention. Extending from the front of vehicle 21, an angular area 24 is sketched, which symbolizes the detection range of distance sensor 10. A dot-dash line 26 depicts the future course path of vehicle 21. Two solid lines 27 designate the future travel-path area of vehicle 21. This future travel-path area results from future course path 26 of vehicle 21, enlarged by the vehicle width and any additional expansions. A distance 23 indicates a lateral transverse offset  $q$  between vehicles 21 and 22. Reference numeral 25 designates a stationary object, for example, a tree at the road edge.

Figure 3 also [depicts] shows a two-lane road 30, on which three vehicles 31, 32, and 33 are represented at two different time points  $t_0$  and  $t_1$ . The positions of the vehicles at time point  $t_0$  are represented in dotted lines and are designated as 31a, 32a, and 33a. The positions of the vehicles at time point  $t_1$  are designated as 31b, 32b, and 33b. Two distances 34 and 35 designate in each case a transverse offset  $q_1$  and  $q_2$  between vehicles 31 and 32 and between vehicles 31 and 33 respectively.

Figure 4 depicts a flowchart in accordance with the [aforementioned] related art. In step 41, using distance sensor 10, vehicles traveling ahead  $F_{vi}$  are detected. In this context, according to Figure 2 and Figure 3, vehicles 22 [as well as] 32 and 33 are detected. In step 42, a position  $P_{vi}$  of each individual vehicle traveling ahead is determined. Depending on the specific configuration, this step can be carried out either by an evaluation circuit within distance sensor 10 or by evaluation and control unit 11. Determined positions  $P_{vi}$  of vehicles traveling ahead  $F_{vi}$  contain a distance  $d_i$  and an angle  $\alpha_i$ . In step 43, a transverse offset  $q_i$  is determined, which in Figures 2 and 3 is indicated by the distances 23, 34, and 35. In purely mathematical terms, transverse offset  $q_i$  yields

$$q_i = d_i * \sin\alpha_i.$$

However, because the curvature of road 20, and 30, and an additional transverse offset of vehicles  $F_{vi}$ , resulting therefrom, are not taken into account in this connection, specific transverse offset  $q_i$  is determined on the basis of position  $P$  of vehicle 31 at time point  $t_1$  and of position  $P_{vi}$  of vehicles traveling ahead 32, 33 at time point  $t_0$ . In other words, transverse offset  $q_i$  in this context is only determined if first vehicle 31 is located at or near the position which the specific vehicle traveling ahead occupied at one or more measuring time points previously.

In step 44, future travel-path area KB of controlled vehicle 21, 31 is determined on the basis of an assumed width  $b$  of the first vehicle, [on the basis of] course path  $KV_i$  of vehicles traveling ahead  $F_{vi}$ , [on the basis of] the latter's specific transverse offset  $q_i$ , and, if appropriate, [on the basis of] previously determined



course paths. In this context, the assumption is made that the first vehicle will continue to move as the vehicle traveling ahead or vehicles. When an intended or commencing lane change of the first vehicle is detected, for example, as a function of a blinker signal, the determined probable travel-path area is expanded in the corresponding direction. This distinguishes determined future travel-path area KB from a pure prediction of the road course. In step 47, the determination of future travel-path area KB of the first vehicle is carried out in an iterative manner, i.e., it is followed by a new determination cycle. In step 45, the determined future travel-path area is limited on the basis of stationary objects 25, and, if present, on the basis of detected oncoming vehicles  $F_g$ , which are not shown in Figures 2 and 3.

Subsequent step 46 relates to the application in the context of an adaptive speed and distance control system. Here, a vehicle traveling ahead is selected as the control target for the distance control system. In this context, only those vehicles traveling ahead are taken into account which are located within determined future travel-path area KB. If a plurality of vehicles traveling ahead are located in this area, then a selection is carried out concerning which of the vehicles traveling ahead requires the smallest desired acceleration, or the greatest desired deceleration, in the controlled vehicle. However, the selection, alternatively or as a supplement, can also be made as a function of other criteria. For example, the selection can be carried out in accordance with which of the vehicles traveling ahead has the least distance from the first, controlled vehicle. Reference numeral 48 designates the iterative repetition of the method.

Figure 5 depicts a further flowchart in accordance with the [above-mentioned] related art. Steps 51 through 54, in this context, correspond to steps 41 through 44 according to the related art in Figure 4. According to this second example [from the related art], in step 55, a determination is made of the verified, future travel-path area KB<sub>ver</sub>. For this purpose, in step 56, further measuring data are used, especially future travel-path area KB<sub>2</sub>, determined elsewhere. This future travel-path area KB<sub>2</sub>, which is determined elsewhere, can be determined, for example, on the basis of the methods known in the related art, using a yaw rate or a transverse acceleration. By linking a plurality of determined future travel-path areas that are independent of each other, the error rate present in a given system is further minimized. In the simplest case, linking two determined future travel-path areas KB and KB<sub>2</sub> is carried out as a result of the fact that first determined travel-path area KB is used as long as an preestablished minimum number of vehicles traveling ahead is detected. If fewer vehicles traveling ahead [are detected] than this preestablished number are detected, then future travel-path area KB<sub>2</sub> is used. Alternatively, the data of both determined travel-path areas KB and KB<sub>2</sub> can also be correlated with each other, to obtain verified travel-path area KB<sub>ver</sub>. In step 58, determining a future verified travel-path area also takes place in an iterative manner. Step 57 corresponds to step 46 from Figure 4 and also contains a target selection of one vehicle traveling ahead in the context of an adaptive speed and distance regulation.

Figure 6 depicts a further flowchart according to the [above-mentioned] related art for a more detailed representation of the method steps for determining future travel-path area KB in steps 44 and 54 of Figures 4 and

5. Accordingly, steps 61 through 63 can be inserted in place of steps 44 and 54 in Figures 4 and 5. In step 61, points of reference  $S_i$  are determined, in that positions  $P_{vi}$  of detected vehicles traveling ahead  $F_{vi}$  are set off against the relevant determined transverse offsets  $q_i$ . In the ideal case, all determined points of reference  $S_i$  will lie on one curve, which corresponds to future course path KV of the first vehicle. In step 62, this course path KV is determined, in that a function is determined, for example, in the form of a polynomial, which at least approximately, to the extent possible, covers all points of reference  $S_i$ . This determined function then describes future course path KV. In step 63, future travel-path area KB is determined, in that course path KV is expanded by width  $b$  of the first vehicle. Additionally, if necessary, a further expansion  $E$  takes place as a function of the detected lane-change signals of the first vehicle.

Figure 7 depicts a schematic diagram[, as an explanation of the method according to] of an embodiment of the present invention. In this context, reference numeral 700 designates the first vehicle, which is traveling on a multilane road 701. In the further course of road 701, two vehicles traveling ahead 702 and 703 are depicted. At the edge of road 701 are also located traffic signs 704, directional posts 705, and trees, which are designated as 706. [It is clear that first] First vehicle 700 is moving on the center lane of three-lane road 701. Vehicle traveling ahead 702 is moving on the right-hand lane relative to vehicle 700, whereas vehicle traveling ahead 703 is moving on the left-hand lane relative to first vehicle 700. First vehicle 700 is equipped with a distance sensor, which detects the positions of vehicles traveling ahead. The detected positions of vehicle traveling ahead 702 are depicted as crosses and are

designated as 707. The detected positions of vehicle traveling ahead 703 are also depicted as crosses and are designated as 708. In the case of vehicle traveling ahead 702, [it is clear that] the positions of vehicle 702 have already been detected by first vehicle 700, the positions being located at least at the same level as first vehicle 700 or even on the path already traveled. Using positions 707, detected in this manner and stored in a storage unit, [it is possible to determine] a comparison curve[,] can be determined which represents course path 709 of vehicle traveling ahead 702. Based on the course path of vehicle traveling ahead 702 and of the known position of first vehicle 700, [it is easy to determine] the transverse offset 711 between first vehicle 700 and course path 709 of vehicle traveling ahead 702 can be determined. Assuming that vehicle traveling ahead 702 is the only vehicle traveling ahead, it would be possible to determine the future course path of first vehicle 700 on the basis of known course path 709 of vehicle traveling ahead 702 and of known transverse offset 711. This future course path of first vehicle 700, if only one reference vehicle 702 is forward, would move by transverse offset 711, shifted parallel to course path 709.

In the case of vehicle traveling ahead 703, no detected positions 708 are yet present, which are located at least at the same level as first vehicle 700. The first detected position of vehicle 703 is designated as 708.a and is situated still in front of the current position of first vehicle 700. On the basis of detected positions 708 of vehicle 703, by analogy to the procedure for vehicle 702, an offset line 710 can be determined, which represents the course path of vehicle traveling ahead 703. If course path 710 of vehicle 703 is projected, or interpolated, in the direction of first vehicle 700, the result is an extension of course path 710 by path 710.a,

which extends up to the current position of first vehicle 700. Based on this projected course path 710.a of vehicle 703, it is possible to determine a transverse offset between the current position of first vehicle 700 and projected course path 710.a of vehicle 703. This transverse offset, designated as 712, with respect to vehicle 703 can therefore be determined, although first vehicle 700 has not yet reached the position of the first detection of vehicle 703, which is designated as 708.a. Therefore, from the point of view of first vehicle 700, two transverse offsets 711 and 712 with respect to vehicles traveling ahead 702 and 703 are known. Furthermore, both course paths 709 and 710 of vehicles traveling ahead 702 and 703 are known. Using this known data, [it is now possible to determine] a future course path of first vehicle 700 on the basis of the two vehicles traveling ahead can now be determined. For this purpose, appropriately taking into account transverse offsets 711 and 712, the average value of course paths 709 and 710 is formed. The result is a determined future course path of first vehicle 700, which is designated in Figure 7 as 713. This determined future course path 713, by analogy to the related art according to Figure 6, is enlarged by the vehicle width as well as by any expansions. Course path 713 of first vehicle 700, expanded in this manner, represents the desired future travel-path area of first vehicle 700. [ For reasons of simplicity, this determined future travel-path area is not depicted in Figure 7.]

Alternatively, in place of determining the transverse offset between first vehicle 700 and course paths 709 and 710 of vehicles traveling ahead 702 and 703, a curvature between the current course path of first vehicle 700 and determined course paths 709 and 710 of vehicles traveling ahead 702 and 703 can be determined. On the basis of

these known curvatures with respect to the course paths of the vehicles traveling ahead, a determination of a future course path of first vehicle 700 is also possible.

5 The determination of the future course path of first vehicle 700 is all the more precise, the greater the number of vehicles traveling ahead detected and their course paths determined. In this case, [the possibility exists to determine] a verified future course path of  
10 first vehicle 700 through comparison, correlation, or an average of the projected course paths of all vehicles traveling ahead can be determined. In this context, projected course paths of vehicles traveling ahead can be filtered out, which, e.g., turn or, as a result of rapid  
15 lane change between the individual traffic lanes, do not yield any reliable course path or one that is suitable for the determination of the future travel-path area.

0905743-053404  
20 Analytically, the conversion of detected relative positional data 707 and 708 of vehicles traveling ahead 702 and 703 is accomplished using statistical analyses and/or using mathematical interpolation procedures. The result of this method is the projected course paths of the vehicles traveling ahead, which are stored in the  
25 storage device of the distance sensor of first vehicle 700. Within the storage device, which is organized preferably as a ring storage device, the stored projected course paths of the vehicles traveling ahead, at selected or freely selectable time points, are compared with the  
30 current coordinate system of the first vehicle. As a result of this conversion, the projected course paths of vehicles traveling ahead, at every time point, exist in the same coordinate system as the coordinate system of first vehicle 700. In order to assume the most relevant  
35 of the determined projected course paths of the vehicles traveling ahead in determining the future course path of

first vehicle 700, the projected course paths of the vehicles traveling ahead are evaluated using a performance index, which contains statistical as well as nonpredictable and predictable components. On the basis of this performance index, in the case of values that lie below a predetermined threshold value, it can be decided whether a projected course path of a vehicle traveling ahead is determined as being irrelevant and therefore is deleted from the storage device, or whether, e.g., the relevance of this projected course path is only conditionally present, and the course path is not to be considered for determining the future travel-path area of the first vehicle. In the event that the storage device of the distance sensor of first vehicle 700 is full and detected relative positional data of further vehicles traveling ahead are present, then, in accordance with a further performance index, which in this case nevertheless only relies on predictable components, the decision is made whether the newly detected course path of a vehicle traveling ahead is so relevant that a previously stored projected course path of a vehicle traveling ahead should be deleted, or whether the newly detected relative positional data should be discarded. Using this method, it [is] can be assured that, at every time point, the most relevant of the projected course paths of the vehicles traveling ahead are present in the storage device.

In the event that, on the basis of particular conditions or circumstances, the determined future travel-path area of first vehicle 700 extends beyond the area of road 701, then the future travel-path area is limited on the basis of stationary objects. This can be, e.g., as [depicted] shown in Figure 7, traffic signs 704, guide posts 705, or trees and/or bushes 706. Also possible is a limitation of the determined future travel-path area on the basis of





## Abstract

5 A method and a device are described for determining a  
future travel-path area of a first vehicle[(700)], which  
is furnished with a distance sensor. In this context,  
using the distance sensor at preestablished or selectable  
time points, at least relative positions [(707, 708)] are  
determined of at least one vehicle traveling ahead [(702,  
703)] with respect to the first vehicle[(700)]. At least  
10 these determined relative positions [(707, 708)] are  
stored in at least one storage device. These relative  
positions[(707, 708)], stored in the storage device,  
constitute in each case a course path [(709, 710)] of the  
corresponding vehicle traveling ahead[(702, 703)]. The  
15 future travel-path area of the first vehicle [(700)] is  
determined at least on the basis of the course path  
[(709, 710)] of the vehicle traveling ahead[(702, 703)].  
The course path [(709, 710)] of the vehicle traveling  
ahead [(702, 703)] is projected in the direction of the  
20 position of the first vehicle[(700)].

[  
(Figure 7)]